

GOMAX INFINITY HOSE

Refrigeration & Air Conditioning Thermoplastic Hoses & Fittings



The excellent chemical capability of the thermoplastic material used in the production of the convoluted inner tube ensures INFINITY hoses are compatible with all HCFC, HFC and hydrocarbon refrigerants. The polyester fibre used for the reinforcement layers guarantees high resistance to stress under pressure. The external cover is manufactured with materials resistant to abrasion and unfavourable environmental conditions.

Maximum Pressure: 42 bar
 Minimum Bursting Pressure: 210 bar
 Temperature Range: -45°C to +130°C

Connections of INFINITY hoses

Type of connection: Brazing with heat ground plate radiator (Patent pending)
 Material used: Drawn steel
 Superficial treatment: White electrolytic galvanizing
 Junction procedure to be used for installation: Strong brazing
 Weld material for installation: Silver-based alloy with low point of fusion

Airefrig Part Number	Description		List Price Ex GST
	Length	Connections	
CAR050	500 mm	1/2" ODS	\$114.78
CAR060	600 mm	1/2" ODS	P.O.A.
CAR100	1000 mm	1/2" ODS	\$147.11
CAR150	1500 mm	1/2" ODS	\$164.76
CAS050	500 mm	5/8" ODS	P.O.A.
CAS100	1000 mm	5/8" ODS	\$148.72
CAS150	1500 mm	5/8" ODS	\$168.00
CAT050	500 mm	3/4" ODS	\$211.96
CAT060	600 mm	3/4" ODS	P.O.A.
CAT100	1000 mm	3/4" ODS	\$266.49
CAT150	1500 mm	3/4" ODS	\$299.91
CAU050	500 mm	7/8" ODS	\$227.90
CAU100	1000 mm	7/8" ODS	\$284.04
CAU150	1500 mm	7/8" ODS	\$317.46
CAV050	500 mm	1-1/8" ODS	\$231.66
CAV100	1000 mm	1-1/8" ODS	\$293.32
CAV150	1500 mm	1-1/8" ODS	\$332.07

