



# Enthalpy

## TD Condensing Units Semi & Hermetic Options (Top Discharge)



Designed and Assembled in Australia by  
Airefrig Australia to suit Australian Conditions  
Available Capacity Range 1.0kw to 34.0kw



### Standard Features

- Weatherproof White Powder Coated Unit Casing
- Copeland, Maneurop & Bitzer Compressors
- Compressor Oil Sight Glass
- Crankcase Heater
- Service Shut Off Valves
- HP/LP Control
- Gomax Flexible Control Hoses
- Liquid Line Drier & Sight Glass
- Oil Separator (Pre-charged with POE Oil)
- Liquid Receiver
- **Supercoat** Condenser Treatment (5000 Hour Salt Spray Test)
- Top Discharge High Ambient Condenser
- Space Saving Unit Design (Can be installed into a corner or back to back)
- ebmpapst Condenser Fans – Single Phase
- Saginomiya Condenser Fan Speed Controller
- Contactor & Overload Block
- Dust & Weatherproof Electrical Box
- Pre-Wired Back to Electrical Box
- 1.22mm (18G) Interconnecting Copper Pipe Work
- Pre-Drilled ready to fit *IPW* series isolating switch
- Discharge Vibration Eliminator
- Suction Accumulator

