

R410A

A-Gas (Australia) Pty Ltd

Chemwatch: 6100-24

Version No: 9.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 06/08/2019

Print Date: 21/09/2020

L.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	R410A
Chemical Name	A-Gas R410A
Synonyms	Suva 9100; R-410A; Suva R-410A; 410A; HFC 410A
Proper shipping name	LIQUEFIED GAS, N.O.S. (contains R125 and R32)
Other means of identification	Not Available
CAS number	133023-17-3

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Refrigerant, for professional users only
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	A-Gas (Australia) Pty Ltd
Address	9-11 Oxford Rd, Laverton North Victoria 3026 Australia
Telephone	93689208
Fax	Not Available
Website	Not Available
Email	Not Available

Emergency telephone number


Association / Organisation	TOLL CHEMICAL LOGISTICS
Emergency telephone numbers	1800024973
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification ^[1]	Gas under Pressure (Liquefied gas)
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
Signal word	Warning

Hazard statement(s)

AUH044	Risk of explosion if heated under confinement.
H280	Contains gas under pressure; may explode if heated.

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

P410+P403	Protect from sunlight. Store in a well-ventilated place.
-----------	--

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

CAS No	%[weight]	Name
75-10-5	30-60	R32
354-33-6	30-60	R125

Mixtures

See section above for composition of Substances

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	<ul style="list-style-type: none">▸ If product comes in contact with eyes remove the patient from gas source or contaminated area.▸ Take the patient to the nearest eye wash, shower or other source of clean water.▸ Open the eyelid(s) wide to allow the material to evaporate.▸ Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.▸ The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.▸ Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s)▸ Transport to hospital or doctor.▸ Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.▸ If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.▸ Ensure verbal communication and physical contact with the patient. <p>DO NOT allow the patient to rub the eyes</p> <p>DO NOT allow the patient to tightly shut the eyes</p> <p>DO NOT introduce oil or ointment into the eye(s) without medical advice</p> <p>DO NOT use hot or tepid water.</p>
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none">▸ Flush skin and hair with running water (and soap if available).▸ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none">▸ Following exposure to gas, remove the patient from the gas source or contaminated area.▸ NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer.▸ Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures.▸ If the patient is not breathing spontaneously, administer rescue breathing.▸ If the patient does not have a pulse, administer CPR.▸ If medical oxygen and appropriately trained personnel are available, administer 100% oxygen.▸ Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction.▸ Keep the patient warm, comfortable and at rest while awaiting medical care.▸ MONITOR THE BREATHING AND PULSE, CONTINUOUSLY.▸ Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary.
Ingestion	<ul style="list-style-type: none">▸ Not considered a normal route of entry.▸ For advice, contact a Poisons Information Centre or a doctor.▸ Avoid giving milk or oils.▸ Avoid giving alcohol.

Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;

A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours

B: Specific drugs and antidotes:

- There is no specific antidote

C: Decontamination

- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. **DO NOT** induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes)

D: Enhanced elimination:

- There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition

- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient

For gas exposures:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.
EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Firefighting measures

Extinguishing media

SMALL FIRE: Use extinguishing agent suitable for type of surrounding fire.
LARGE FIRE: Cool cylinder.
DO NOT direct water at source of leak or venting safety devices as icing may occur.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▸ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	<p>GENERAL</p> <ul style="list-style-type: none">▸ Alert Fire Brigade and tell them location and nature of hazard.▸ Wear breathing apparatus and protective gloves.▸ Fight fire from a safe distance, with adequate cover.▸ Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	<ul style="list-style-type: none">▸ Containers may explode when heated - Ruptured cylinders may rocket▸ Fire exposed containers may vent contents through pressure relief devices.▸ High concentrations of gas may cause asphyxiation without warning.▸ May decompose explosively when heated or involved in fire.

	<ul style="list-style-type: none">▸ Contact with gas may cause burns, severe injury and/ or frostbite. Decomposition may produce toxic fumes of: carbon monoxide (CO) carbon dioxide (CO2) hydrogen chloride phosgene hydrogen fluoride other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.
HAZCHEM	2TE

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none">▸ Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used.▸ DO NOT enter confined spaces where gas may have accumulated.▸ Increase ventilation.
Major Spills	<ul style="list-style-type: none">▸ Clear area of all unprotected personnel and move upwind.▸ Alert Emergency Authority and advise them of the location and nature of hazard.▸ Wear breathing apparatus and protective gloves.▸ Prevent by any means available, spillage from entering drains and water-courses.▸ Remove leaking cylinders to a safe place.▸ Fit vent pipes. Release pressure under safe, controlled conditions▸ Burn issuing gas at vent pipes.▸ DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none">·Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature·The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines.·Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended.·Before connecting gas cylinders, ensure manifold is mechanically secure and does not containing another gas. <ul style="list-style-type: none">▸ Vented gas is more dense than air and may collect in pits, basements.
Other information	<ul style="list-style-type: none">▸ Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open.▸ Such compounds should be sited and built in accordance with statutory requirements.▸ The storage compound should be kept clear and access restricted to authorised personnel only.▸ Cylinders stored in the open should be protected against rust and extremes of weather. DO NOT store above 50 deg. C.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none">▸ DO NOT use aluminium or galvanised containers▸ Cylinder:▸ Ensure the use of equipment rated for cylinder pressure.▸ Ensure the use of compatible materials of construction.▸ Valve protection cap to be in place until cylinder is secured, connected.▸ Cylinder must be properly secured either in use or in storage.
Storage incompatibility	<ul style="list-style-type: none">▸ Avoid reaction with oxidising agents▸ Avoid magnesium, aluminium and their alloys, brass and steel.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
R32	Methylene fluoride; (Difluoromethane; HFC-32)	3,000 ppm	6,500 ppm	39,000 ppm


Ingredient	Original IDLH	Revised IDLH
R32	Not Available	Not Available
R125	Not Available	Not Available

MATERIAL DATA

May act as a simple asphyxiants; these are gases which, when present in high concentrations, reduce the oxygen content in air below that required to support breathing, consciousness and life; loss of consciousness, with death by suffocation may rapidly occur in an oxygen deficient atmosphere.

CARE: Most simple asphyxiants are odourless or possess low odour and there is no warning on entry into an oxygen deficient atmosphere. If there is any doubt, oxygen content can be checked simply and quickly. It may not be appropriate to only recommend an exposure standard for simple asphyxiants rather it is essential that sufficient oxygen be maintained.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▸ Safety glasses with side shields ▸ Chemical goggles. ▸ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▸ When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▸ Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change) ▸ Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated. ▸ Protective overalls, closely fitted at neck and wrist. ▸ Eye-wash unit. ▸ Ensure availability of lifeline in confined spaces. ▸ Staff should be trained in all aspects of rescue work.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AX-AUS / Class1 P3	-
up to 50	1000	-	AX-AUS / Class 1 P3
up to 50	5000	Airline *	-
up to 100	5000	-	AX-2 P3
up to 100	10000	-	AX-3 P3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Colourless liquefied gas with slight ether-like odour.		
Physical state	Liquefied Gas	Relative density (Water = 1)	1.062 @ 25 deg C

Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	~7	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	-51.6	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	>1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	1653 @ 25 deg C, 3052 @ 50 deg C	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur. ▶ Extremely high temperatures.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	<p>Symptoms of asphyxia (suffocation) may include headache, dizziness, shortness of breath, muscular weakness, drowsiness and ringing in the ears. If the asphyxia is allowed to progress, there may be nausea and vomiting, further physical weakness and unconsciousness and, finally, convulsions, coma and death. Significant concentrations of the non-toxic gas reduce the oxygen level in the air. As the amount of oxygen is reduced from 21 to 14 volume %, the pulse rate accelerates and the rate and volume of breathing increase.</p> <p>The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.</p> <p>Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.</p>
Ingestion	<p>Overexposure is unlikely in this form.</p> <p>Not normally a hazard due to physical form of product.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p>
Skin Contact	<p>Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>In common with other halogenated aliphatics, fluorocarbons may cause dermal problems due to a tendency to remove natural oils from the skin causing irritation and the development of dry, sensitive skin. They do not appear to be appreciably absorbed.</p>
Eye	<p>Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).</p>
Chronic	<p>Principal route of occupational exposure to the gas is by inhalation.</p> <p>It is generally accepted that the fluorocarbons are less toxic than the corresponding halogenated aliphatic based on chlorine. Repeated inhalation exposure to the fluorocarbon FC-11 does not produce pathologic lesions of the liver and other visceral organs in experimental animals. There has been conjecture in non-scientific publications that fluorocarbons may cause leukemia, cancer, sterility and birth defects; these have not been verified by current research. The high incidence of cancer, spontaneous abortion and congenital anomalies amongst hospital personnel, repeatedly exposed to fluorine-containing general anaesthetics, has caused some scientists to call for a lowering of the</p>

	fluorocarbon exposure standard to 5 ppm since some are mutagens. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.	
R410A	TOXICITY	IRRITATION
	Not Available	Not Available
R32	TOXICITY	IRRITATION
	Inhalation (rat) LC50: >759132.84 mg/l/4h*) ^[2]	Not Available
	Inhalation (rat) LC50: 1890 mg/l/4H ^[2]	
R125	TOXICITY	IRRITATION
	Inhalation (rat) LC50: 2910 mg/l/4H ^[2]	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

R410A	Acute toxicity - Inhalation, LC 0, 4 h, rat, > 52 % v/v air (R125/R32) Irritation - No irritation signs noted during toxicity testing. (R125/R32) Chronic toxicity - Inhalation, after a single exposure, dog, >= 10% v/v air, cardiac sensitization following adrenergic stimulation (Data relative to R125) - Inhalation, after repeated exposure, rat, Target organ: central nervous system, >= 5% v/v air (R32) - No mutagenic, teratogenic effects (R125/R32) - Foetotoxic effect (R32)
R125	Cardiac sensitisation threshold limit >245400 mg/m3 Anaesthetic effects threshold limit 490800 mg/m3 * DuPont SDS

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

R410A	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
R32	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	1-507mg/L	2
	EC50	48	Crustacea	1-573mg/L	2
	EC50	96	Algae or other aquatic plants	1-888mg/L	2
R125	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>81.8mg/L	2
	EC50	48	Crustacea	>97.9mg/L	2
	EC50	72	Algae or other aquatic plants	>114mg/L	2
R125	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC	96	Fish	10mg/L	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Mobility - Air, Henrys law constant (H) ca. 150kPa.m3/mol Result: considerable volatility Conditions: 20 °C / calculated value (Data relative to R125) - Air, Henrys law constant (H) ca. 19.7kPa.m3/mol Result: considerable volatility Conditions: 25 °C / calculated value (R32) - Soil/sediments, adsorption, log KOC from 1.05 - 1.7 Conditions: calculated value (R125/R32) Persistence and degradability Abiotic degradation - Air, indirect photo-oxidation, t 1/2 = 28.2 year(s) Conditions: sensitizer: OH radicals Degradations products: carbon dioxide / fluorhydric acid / trifluoroacetic acid (Data relative to R125) - Air, indirect photo-oxidation, t 1/2 = 4.16 year(s) Conditions: sensitizer: OH radicals Degradations products: carbon dioxide / fluorhydric acid (R32) - Air, photolysis, ODP = 0 Result: no effect on stratospheric ozone Reference value for CFC 11: ODP = 1. (R125/R32) - Air, greenhouse effect, GWP < 0.5> Reference value for CFC 11: GWP = 1. (R125/R32) Biotic degradation - Aerobic, test ready biodegradability/closed bottle, degradation from 4 - 5 %, 28 day(s) Result: non-readily biodegradable (R125/R32) Bioaccumulative potential - Bioconcentration: log Po/w from 0.21 - 1.48 Result: non-bioaccumulable Conditions:

measured value (R125/R32)
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
R32	LOW	LOW
R125	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
R32	LOW (LogKOW = 0.2)
R125	LOW (LogKOW = 1.5472)

Mobility in soil

Ingredient	Mobility
R32	LOW (KOC = 23.74)
R125	LOW (KOC = 154.4)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none">▸ Evaporate residue at an approved site.▸ Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.▸ Ensure damaged or non-returnable cylinders are gas-free before disposal.
------------------------------	---

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2TE

Land transport (ADG)

UN number	3163	
UN proper shipping name	LIQUEFIED GAS, N.O.S. (contains R125 and R32)	
Transport hazard class(es)	Class	2.2
	Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	274 392
	Limited quantity	120 ml

Air transport (ICAO-IATA / DGR)

UN number	3163	
UN proper shipping name	Liquefied gas, n.o.s. * (contains R125 and R32)	
Transport hazard class(es)	ICAO/IATA Class	2.2
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	2L
Packing group	Not Applicable	
Environmental hazard	Not Applicable	

Special precautions for user	Special provisions	Not Applicable
	Cargo Only Packing Instructions	200
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	200
	Passenger and Cargo Maximum Qty / Pack	75 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	3163	
UN proper shipping name	LIQUEFIED GAS, N.O.S. (contains R125 and R32)	
Transport hazard class(es)	IMDG Class	2.2
	IMDG Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number	F-C , S-V
	Special provisions	274
	Limited Quantities	120 mL

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

R32 is found on the following regulatory lists
Australian Inventory of Industrial Chemicals (AIIC)
R125 is found on the following regulatory lists
Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status
Australia - AIIC	Yes
Australia Non-Industrial Use	No (R32; R125)
Canada - DSL	Yes
Canada - NDSL	No (R32; R125)
China - IECSC	No (R32)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	06/08/2019
Initial Date	19/01/2007

SDS Version Summary

Version	Issue Date	Sections Updated
8.1.1.1	16/03/2017	Acute Health (inhaled), Acute Health (skin), Chronic Health, Classification, Handling Procedure, Ingredients, Storage (suitable container)
9.1.1.1	31/01/2019	Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Chronic Health, Environmental, Exposure Standard, First Aid (skin), First Aid (swallowed), Handling Procedure, Personal Protection (other), Personal Protection (Respirator), Personal Protection (eye), Personal Protection (hands/feet), Spills (major), Storage (storage incompatibility), Storage (storage requirement), Toxicity and Irritation (Other), Transport Information

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.